

LED Vapor Tight

Series ZY-STPA/STP



Features

- Optional 100% DR lens additive for impact resistance;
- IP 65 for wet locations;
- Suitable for ceiling or suspended mount;
- Excellent light distribution and uniformity;
- Emergency battery backup option;
- 5 Year Manufacturer's Warranty.



Application

Widely used in Factory, Office, Workshop, Warehouse, Restaurant, Logistics Center, Exhibition Hall, Gymnasium, Supermarket, Other Places where need indoor or outdoor illumination.


Technical Data

Color Temperature	2700K to 5700K	Input Voltage with ballast	100-277V
Beam Angle	120 degree	Frequency	50/60Hz
Color Consistency	4 steps	Power Factor	More than 0.99
CRI	More than 80	Life span	50,000 hours
Operation Temperature	-30-45°C	Led Type	SMT 2835
Efficiency with ballast	More than 135 LPW	Housing	Glass Fibre+PC
Emergency Battery Volume	2.600MAH (5,200MAH optional)	Emergency Time	1.5 Hours (3 Hours optional)


Basic Data

Model	ZY-STP8132-24W	ZY-STP8232-35W	ZY-STP8217-18W	ZY-STP8217-30W	ZY-STP8232-48W	ZY-STP8332-72W	ZY-STP8432-95W
Power	24W	35W	18W	30W	48W	72W	95W
Lumens	3120	4550	2340	3900	6240	9360	12350
Emergency Lumens	1040±50						
Size(cm)(L×W×H)	126.8×10×11.5	126.8×16.5×11.5	66.8×16.5×11.5		126.8×16.5×11.5	127×26.4×11.5	127×44.1×11.5

Dimensions




ZY-STP8432-95W



ZY-STP8332-72W



ZY-STP8232-35W/ZY-STP8232-48W



ZY-STP8132-24W



ZY-STP8217-18W/30W